

GUTTELING CHEM 14 PS



CHEMICALS & PHARMACEUTICALS

Composite hoses/Chemical and corrosive products



APPLICATIONS

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste and all petroleum products with aromatic content up to 100%.
For road and rail tanker equipment or fixed installations in the chemical industry.

ADVANTAGES

- Easy to handle due to hose flexibility (low bending radius).
- Usable at a wide range of temperatures.
- Capable of handling many different chemicals.

COUPLING/FITTINGS

All types of swaged couplings:

- standard or revolving Guillemín
- standard or secured camlock coupling
- threaded male or female fitting (BSP, NPT, etc.)
- fixed or swivel flange ISO PN10/16, PN20 (ASA150), TTMA, etc.

COMPLEMENTARY INFORMATION

Fitted lengths are delivered on request with pressure test certificate.
Imperial size on request.

TECHNICAL DESCRIPTION

Internal Helix	polypropylene coated steel.
Inner tube	polypropylene film.
Reinforcement	polypropylene layers
Cover	PVC coated fabric, grey, corrugated.
External Helix	stainless steel.
Temperature range	-30°C => +100°C
Electrical Properties	resistance between end fittings ≤100Ω/assembly.


STANDARD/APPROVAL



EN 13765: Bureau Veritas type approval N°7232905/8/049/TBE.

EN

-

TMD



 CHEMICALS & PHARMACEUTICALS		GUTTELING CHEM 14 PS					
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	37.0	14	56	100	0.76	30	30103866
32.0	43.0	14	56	120	0.93	30	30103862
40.0	52.0	14	56	140	1.60	1	30103890
50.0	62.0	14	56	180	1.76	30	30103837
65.0	78.5	14	56	200	2.90	30	30103908
80.0	95.0	14	56	280	3.13	30	30103972
100.0	121.0	14	56	400	5.33	30	30103949

Tolerance on length: ±1% (ISO 1307 Standard).