

STEAM 16



OIL & GAS

Steam



APPLICATIONS

High pressure steam hose.

ADVANTAGES

- Highly flexible.
- Resistant to abrasion.
- Steel braid reinforcement.

COMPLEMENTARY INFORMATION

2 standard colors available.
Type BK = Black
Type RE = Red


TECHNICAL DESCRIPTION

Inner tube	synthetic EPDM rubber, black, smooth.
Reinforcement	steel braid
Cover	synthetic EPDM rubber, black or red, fabric impression.
Working temperature	-30°C => +210°C.
Electrical Properties	R<1MΩ/Ig.

STANDARD/APPROVAL

BS 5342:1985 type 2 class A.

BS



**OIL & GAS****STEAM 16**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	TYPE	ARTICLE NUMBER
13.0	24.0	16	160	150	0.47	40.0	BK	5513652
13.0	24.0	16	160	150	0.51	40.0	RE	5513659
16.0	28.0	16	160	190	0.59	40.0	BK	5513653
16.0	28.0	16	160	190	0.64	40.0	RE	5513660
19.0	32.0	16	160	230	0.73	40.0	BK	5513654
19.0	32.0	16	160	230	0.80	40.0	RE	5513661
19.0	32.0	16	160	230	0.80	60.0	RE	5514008
25.0	38.0	16	160	300	0.93	40.0	BK	5513655
25.0	38.0	16	160	300	1.00	40.0	RE	5513662
25.0	38.0	16	160	300	1.00	60.0	RE	5514009
32.0	48.0	16	160	380	1.44	40.0	BK	5513656
32.0	48.0	16	160	320	1.44	40.0	RE	5513663
38.0	54.0	16	160	380	1.75	40.0	BK	5513657
38.0	54.0	16	160	380	1.75	40.0	RE	5513664
51.0	69.0	16	160	500	2.31	40.0	BK	5513658
51.0	69.0	16.0	160.0	500	2.31	40.0	RE	5513665

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

