

STEAM 16 RED



OIL & GAS

Vapeur



APPLICATIONS

Tuyau vapeur haute pression.

CARACTÉRISTIQUES TECHNIQUES

Inner tube	caoutchouc synthétique EPDM, noir, lisse.
Reinforcement	tressée acier
Cover	caoutchouc synthétique EPDM, rouge, aspect grain toile.
Temperature range	-30°C => +210°C
Electrical Properties	R<1MΩ/ig.

NORMES/HOMOLOGATIONS

BS



TRELLEBORG

STEAM 16 RED - BS5342:1985 - 2A - 16 BAR - ND - month/year



13-25mm:



TRELLEBORG

STEAM 16 RED - BS5342:1985 - 2A - 16 BAR - ND - month/year



32-51mm:



OIL & GAS

STEAM 16 RED



DIAMÈTRE INTÉRIEUR (MM)	DIAMÈTRE EXTÉRIEUR (MM)	PRESSION DE SERVICE (BAR)	PLNE (BAR)	RAYON DE COURBURE (MM)	POIDS (KG/M)	LONGUEUR (M)	CODE ARTICLE
13.0	24.0	16	160	150	0.51	40	5513659
16.0	28.0	16	160	190	0.64	40	5513660
19.0	32.0	16	160	230	0.80	40	5513661
19.0	32.0	16	160	230	0.80	60	5514008
25.0	38.0	16	160	300	1.00	40	5513662
25.0	38.0	16	160	300	1.00	60	5514009
32.0	48.0	16	160	320	1.44	40	5513663
38.0	54.0	16	160	380	1.75	40	5513664

Tolérance sur longueur : $\pm 1\%$ (norme ISO 1307).

