

# PUMPADUKT L



## OIL & GAS

Oil and petroleum/Suction and discharge for road and rail tankers



### APPLICATIONS

Suction and discharge of petroleum products with aromatics up to 50%.  
Equipment of road tank trucks for oil and petrol deliveries and their loading/unloading bays.

### ADVANTAGES

A highly light weight and flexible hose for easy handling. The corrugated cover allows extreme bendings.

### TECHNICAL DESCRIPTION

Inner tube	oil and petrol resistant NBR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	oil and weather resistant CR, black, fabric impression, corrugated.
Temperature range	-40°C => +100°C
Electrical Properties	conductive tube, $R < 10^6 \Omega / \text{lg}$ .

### STANDARD/APPROVAL

EN 1761.

EN



and embossed: TRELLEBORG - PUMPADUKT L - NBR 1 - EN 1761:1999 - SD - ND - WP 10bar - ?/T - month/year - batch number



OIL & GAS

PUMPADUKT L



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
50.0	66.0	10	40	100	2.01	20	5013683
50.0	66.0	10	40	100	2.01	40	5013684
75.0	91.0	10	40	150	3.18	20	5013518
75.0	91.0	10	40	150	3.18	40	5013519
100.0	116.0	10	40	200	3.99	40	5013686

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

