

# CANALKLER 250 S ASSEMBLY



## CONSTRUCTION & INFRASTRUCTURE

Drain and sewer cleaning



### APPLICATIONS

Sewer jetting and heavy duty, high pressure water cleaning.

### ADVANTAGES

- Very low sliding resistance which allows: higher cleaning efficiency, reduction of cleaning time and therefore, reduction of fuel consumption.
- Longer lifespan thanks to the special cover compound with higher abrasion resistance.
- Better flexibility, even at low temperatures.
- Easy to handle and user friendly.
- Deformation resistance.
- Extra high strength and security due to aramide reinforcement.

### COUPLING/FITTINGS


All hoses are assembled with BSP female/BSP male.  
All assembled hoses are pressure tested at 375bar and have an unique hose number.

### COMPLEMENTARY INFORMATION

Delivered with test certificate on each factory assembled hose.

### TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	aramide textile, braided
Cover	SBR/NR, black, smooth. Very low sliding resistance.
Working temperature	-30°C => +80°C.



Embossed branding



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	25.6	250	625	70	0.45	40.0	5014178
13.0	25.6	250	625	70	0.45	60.0	5014179
13.0	25.6	250	625	70	0.45	80.0	5014180
13.0	25.6	250	625	70	0.45	100.0	5014916
13.0	25.6	250	625	70	0.45	120.0	5014005
19.0	31.6	250	625	90	0.61	40.0	5014181
19.0	31.6	250	625	90	0.61	80.0	5014182
19.0	31.6	250	625	90	0.61	100.0	5014459
19.0	31.6	250	625	90	0.61	120.0	5014006
25.0	39.3	250	625	100	0.90	40.0	5014183
25.0	39.3	250	625	100	0.90	50.0	5014874
25.0	39.3	250	625	100	0.90	80.0	5014184
25.0	39.3	250	625	100	0.90	100.0	5014238
25.0	39.3	250	625	100	0.90	120.0	5014007
25.0	39.3	250	625	100	0.90	150.0	5014461
25.0	39.3	250	625	100	0.90	160.0	5014185
25.0	39.3	250	625	100	0.90	180.0	5014186
25.0	39.3	250	625	100	0.90	200.0	5014520
25.0	39.3	250	625	100	0.90	240.0	5014733
32.0	47.6	250	625	130	1.12	40.0	5014187
32.0	47.6	250	625	130	1.12	80.0	5014188
32.0	47.6	250	625	130	1.12	120.0	5014008
32.0	47.6	250	625	130	1.12	150.0	5014466
32.0	47.6	250	625	130	1.12	160.0	5014189
32.0	47.6	250	625	130	1.12	180.0	5014190
32.0	47.6	250	625	130	1.12	200.0	5014655
38.0	54.0	250	500	155	1.35	120.0	5014009

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

