

# AQUA 10 SD



## AGRICULTURE



Water/Suction applications

### APPLICATIONS

Water suction and delivery hose used for industrial water, waste water and agricultural equipment.

### TECHNICAL DESCRIPTION

|                     |   |
|---------------------|---|
| Inner tube          | SBR, black, smooth.                         |
| Reinforcement       | synthetic textile with embedded steel helix |
| Cover               | SBR, black, fabric impression.              |
| Working temperature | -30°C => +80°C.                             |
| Special Properties  | Max. vacuum: 0.9 bar.                       |

10 SD



AQUA 10 SD





AGRICULTURE

AQUA 10 SD



| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 25.0    | 35.0    | 10                     | 30                      | 100                 | 0.71          | 40.0       | 5503700        |
| 32.0    | 42.0    | 10                     | 30                      | 120                 | 1.01          | 40.0       | 5503701        |
| 38.0    | 48.0    | 10                     | 30                      | 160                 | 1.19          | 40.0       | 5503702        |
| 51.0    | 63.0    | 10                     | 30                      | 200                 | 1.72          | 40.0       | 5503703        |
| 63.0    | 75.0    | 10                     | 30                      | 245                 | 2.23          | 20.0       | 59007854       |
| 63.0    | 75.0    | 10                     | 30                      | 245                 | 2.23          | 40.0       | 5503704        |
| 76.0    | 88.0    | 10                     | 30                      | 320                 | 2.57          | 20.0       | 59007855       |
| 76.0    | 88.0    | 10                     | 30                      | 320                 | 2.57          | 40.0       | 5503705        |
| 90.0    | 103.0   | 10                     | 30                      | 360                 | 3.36          | 20.0       | 59007856       |
| 90.0    | 103.0   | 10                     | 30                      | 360                 | 3.36          | 40.0       | 5503706        |
| 102.0   | 116.0   | 10                     | 30                      | 410                 | 4.05          | 20.0       | 59007857       |
| 102.0   | 116.0   | 10                     | 30                      | 410                 | 4.05          | 40.0       | 5503695        |
| 127.0   | 143.0   | 10                     | 30                      | 510                 | 5.82          | 20.0       | 59007858       |
| 127.0   | 143.0   | 10                     | 30                      | 510                 | 5.82          | 40.0       | 5503696        |
| 152.0   | 169.0   | 10                     | 30                      | 610                 | 7.66          | 20.0       | 59007859       |
| 152.0   | 169.0   | 10                     | 30                      | 610                 | 7.66          | 40.0       | 5503697        |
| 203.0   | 225.0   | 10                     | 30                      | 1000                | 13.28         | 20.0       | 59007860       |
| 203.0   | 225.0   | 10                     | 30                      | 1000                | 13.28         | 40.0       | 5503698        |
| 254.0   | 276.0   | 10                     | 30                      | 1270                | 19.17         | 20.0       | 59007861       |

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

