

ASSAINIX



CONSTRUCTION & INFRASTRUCTURE

Drain and sewer cleaning



APPLICATIONS

Pumping installations, suction and delivery.
Sewer and tank truck applications.

ADVANTAGES

Excellent kink resistance even at small bending radius.
Withstands 0.8bar vacuum.
Smooth cover to prevent friction on sharp edges of manholes, walls fences, etc.
This hose can be produced with straight or enlarged ends (from 3 to 12mm) to fit all types of couplings.
High resistance to abrasive environment.

COMPLEMENTARY INFORMATION

Other lengths and other diameters like diam.120mm could be produced on request.

TECHNICAL DESCRIPTION

Inner tube	NR, black, smooth.
Reinforcement	synthetic textile cords with embedded steel helix
Cover	NR, black, fabric impression.
Working temperature	-30°C => +60°C.
Special Properties	Max. vacuum: 0.9 bar.





**CONSTRUCTION &
INFRASTRUCTURE**

ASSAINIX



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
100.0	120.0	4	12	800	5.21	4.5	0060278
120.0	140.0	4	12	960	7.29	4.5	0095036
120.0	140.0	4	12	960	7.30	6.0	5006886

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

