

TRUCK 7



CONSTRUCTION & INFRASTRUCTURE

Bulk tank truck discharge




APPLICATIONS

Delivery hose to transfer abrasive material such as cement, sand, etc.

TECHNICAL DESCRIPTION

Inner tube	natural rubber, black, smooth.
Reinforcement	synthetic textile and antistatic wire
Cover	synthetic SBR rubber, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	Conductive tube. ATEX and TRGS 727 approval for hazardous areas.



 CONSTRUCTION & INFRASTRUCTURE		TRUCK 7				
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
75.0	93.0	7	21	2.77	40.0	5513666
90.0	101.0	7	21	2.00	40.0	5513795
90.0	106.0	7	21	2.89	40.0	5513667
100.0	120.0	7	21	4.08	40.0	5513668
102.0	119.0	7	21	3.00	40.0	5513713
102.0	122.0	7	21	4.00	40.0	5513714
110.0	123.0	7	21	3.00	40.0	5513796
127.0	145.0	7	21	4.49	40.0	5513669
152.0	172.0	7	21	5.61	40.0	5513670

Tolerance on length: ±1% (ISO 1307 Standard).

