

OIL 20 D



OIL & GAS

Oil and petroleum/Oil cargo



APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%, mainly for oil platforms, marine fueling, storage tanks or other industrial facilities.
Limited use for biofuels. Consult us.

ADVANTAGES

- Weather, flame, oil projection, UV and ozone resistant.
- Up to 60m long.


TECHNICAL DESCRIPTION

Inner tube	NBR, black, smooth.
Reinforcement	synthetic textile
Cover	CR, black, fabric impression.
Working temperature	-30°C => +85°C.
Electrical Properties	crossing antistatic wires and conductive tube, $R < 10^6 \Omega / \text{lg}$.



TRELLEBORG

OIL 20 D



and embossed: TRELLEBORG - OIL 20 D - ND - WP 20 bar - month/year - batch number

**OIL & GAS****OIL 20 D**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
76.0	92.0	20	60	304	2.42	60.0	5607748
102.0	118.0	20	60	815	3.77	60.0	59011978
127.0	145.0	20	60	1015	5.32	60.0	59011979
152.0	172.0	20	60	1520	7.12	60.0	59011980
203.0	235.0	20	60	2030	15.19	40.0	59013044
254.0	292.0	20	60	2540	23.28	20.0	59013045

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

