

# GUTTELING CHEM 10 SS

## APPLICATIONS

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste and all petroleum products with aromatic content up to 100%.  
For road and rail tanker equipment or fixed installations in the chemical industry.

## ADVANTAGES

Easy to handle due to hose flexibility (low bending radius).  
Usable at a wide range of temperatures.  
Capable of handling many different chemicals.

## COUPLING/FITTINGS

All types of swaged couplings:  
- standard or revolving Guillemín  
- standard or secured camlock coupling  
- threaded male or female fitting (BSP, NPT, etc.)  
- fixed or swivel flange ISO PN10/16, PN20 (ASA150), TTMA, etc.

## COMPLEMENTARY INFORMATION

Fitted lengths are delivered on request with pressure test certificate.  
Imperial size on request.

## TECHNICAL DESCRIPTION

Internal Helix	stainless steel 304L (stainless steel 316L on request).
Inner tube	polypropylene film.
Reinforcement	polypropylene layers
Cover	PVC coated fabric, grey, corrugated.
External Helix	stainless steel.
Temperature range	-30°C => +100°C
Electrical Properties	resistance between end fittings ≤100Ω/assembly.


## STANDARD/APPROVAL

EN 13765: Bureau Veritas type approval N°7232905/8/049/TBE.

EN

-

TMD



GUTTELING CHEM 10 SS

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
50.0	62.0	10	40	180	1.70	1	30103732
65.0	78.5	10	40	200	2.80	1	30103944
80.0	95.0	10	40	280	3.23	1	30103764
80.0	95.0	10	40	280	3.23	1	30104655
100.0	118.0	10	40	400	3.96	1	30103822

Tolerance on length: ±1% (ISO 1307 Standard).