

# BOAT SANITARY HOSE


**MARINE EQUIPMENT**

Boat equipment/Water



## APPLICATIONS

Wastewater disposal (domestic and sanitary) on pleasure boats.


## ADVANTAGES

- Flexible.
- Kink resistant.
- Diffusion tight (will not be tainted by odour from the toilet system).

## TECHNICAL DESCRIPTION

Inner tube	chlorobutyl, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	EPDM, white, fabric impression.
Working temperature	-30°C => +100°C.
Special Properties	Max. pressure: 0.8 bar.

**Y HOSE**

**TRELLEBORG**
**BOAT SANITARY HOSE**


**MARINE EQUIPMENT****BOAT SANITARY HOSE**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
16.0	27.0	10	32	64	0.54	20.0	59013247
16.0	27.0	10	32	64	0.54	40.0	59013248
20.0	31.0	10	32	80	0.63	20.0	59013249
20.0	31.0	10	32	80	0.64	40.0	59013250
25.0	36.0	10	32	100	0.75	20.0	59013251
25.0	36.0	10	32	100	0.75	40.0	59013252
32.0	43.0	10	32	130	0.94	20.0	59013253
32.0	43.0	10	32	130	0.94	40.0	59013254
38.0	49.0	10	32	160	1.10	40.0	59013308

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

