

# VINITRELL



## FOOD & BEVERAGE

Food industry/Transfer



### APPLICATIONS

Specially designed for wine transfers in wine processing industries and for transfer of fresh grapes on the largest diameters.  
Suction and discharge of any foodstuff except fatty/oily liquids.

### ADVANTAGES

- The utmost user friendly rubber hose: outstanding flexibility and easy handling thanks to slicking cover, non-marking with weak tractive effort.
- Food grade white tube complying with the most stringent European and American requirements for foodstuff handling.
- Unaffected by changes in temperature.
- Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 110°C during 10 minutes max.
- Contains no phthalate.

### COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### COMPLEMENTARY INFORMATION

Please refer to our cleaning guidelines, available upon request and from our website.

### TECHNICAL DESCRIPTION

Inner tube	food grade quality NR, white, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	special polymer-based, red.
Temperature range	-30°C => +80°C

### STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

EU

FDA regulation No. 21 CFR 177.2600.

FDA

French legislation.

RF



All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.



and embossed: TRELLEBORG - VINITRELL - FDA - WP 10bar - week/year - batch number - Made in France



and embossed: TRELLEBORG - VINITRELL - FDA - WP 6bar - week/year - batch number - Made in France

 FOOD & BEVERAGE		VINITRELL					
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
38.0	51.5	10	30	80	1.15	20	5513028
38.0	51.5	10	30	80	1.15	40	5600349
50.0	65.0	10	30	100	1.57	20	5026130
50.0	65.0	10	30	100	1.57	40	5026129
63.0	77.0	10	30	130	1.87	20	5026132
63.0	77.0	10	30	130	1.87	40	5026131
70.0	86.5	10	30	140	2.42	20	5026133
70.0	86.5	10	30	140	2.42	40	5026134
75.0	91.5	10	30	150	2.54	20	5026135
75.0	91.5	10	30	150	2.54	40	5026136
100.0	117.0	6	18	140	3.32	20	5026072
125.0	142.5	6	18	170	4.10	10	5501457
125.0	142.5	6	18	170	4.10	20	5501458
150.0	167.5	6	18	200	4.97	10	5501459
150.0	167.5	6	18	200	4.97	20	5501460

Tolerance on length: ±1% (ISO 1307 Standard).

