

PULSOR GRAVITY



CONSTRUCTION & INFRASTRUCTURE

Concrete pump and placement



APPLICATIONS

Lay flat hose for concrete bucket (skip).
For discharge to concrete form.

ADVANTAGES

Coil flat for easy storage and handling.
Lightweight hose.
Excellent resistance to wear, abrasion and weather.
Abrasion resistance of tube $<100\text{mm}^3$.


TECHNICAL DESCRIPTION

Inner tube	NR/SBR, black, smooth.
Reinforcement	synthetic textile
Cover	NR/SBR, black, fabric impression.
Working temperature	$-30^{\circ}\text{C} \Rightarrow +90^{\circ}\text{C}$.



TRELLEBORG

PULSOR GRAVITY





**CONSTRUCTION &
INFRASTRUCTURE**

PULSOR GRAVITY



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
152.0	160.4	3	10	1.95	40.0	5513541
203.0	212.0	3	10	3.80	40.0	5513542
254.0	263.0	3	10	4.70	40.0	5513543

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

