

ASPIKLER N



CONSTRUCTION & INFRASTRUCTURE

Drain and sewer cleaning



APPLICATIONS

For sewer suction.
Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.


ADVANTAGES

High resistance to abrasive environment and abrasive transportation media.
Suitable both for suction and pressure.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile cords with embedded steel helix
Cover	SBR/NR, black, fabric impression.
Working temperature	-30°C => +80°C.
Special Properties	Max. vacuum: 0.9 bar.


ASPIKLER N

TRELLEBORG
ASPIKLER N




**CONSTRUCTION &
INFRASTRUCTURE**

ASPIKLER N



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
100.0	116.5	6	15	450	4.30	20.0	0095016
100.0	116.5	6	15	450	4.30	40.0	0096724
102.0	118.0	6	15	450	4.38	20.0	5513565
125.0	144.0	6	15	550	6.30	20.0	0094152
125.0	144.0	6	15	550	6.30	40.0	5009671
127.0	146.0	6	15	550	6.39	20.0	5513566
150.0	170.0	6	15	650	7.77	20.0	5008847
152.0	172.0	6	15	650	7.87	20.0	5513567

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

