

BERGALAV



FOOD & BEVERAGE

Food industry/Cleaning



APPLICATIONS

For hot water cleaning in food processing plants with possible occasional use with steam up to 160°C.

ADVANTAGES

- Highly flexible.
- Specially adapted to keep round on reels.
- Contains no phthalate.

COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

TECHNICAL DESCRIPTION

Inner tube	EPDM, white, smooth.
Reinforcement	synthetic textile
Cover	weather resistant EPDM, blue, smooth.
Working temperature	Water: -30°C to +100°C. Occasional steam : 160°C.

STANDARD/APPROVAL

FDA regulation No. 21 CFR 177.2600.

FDA



and embossed: week/year - batch number

**FOOD & BEVERAGE****BERGALAV**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
10.0	18.0	10	30	75	0.25	20.0	5501308
10.0	18.0	10	30	75	0.25	40.0	5501309
13.0	22.0	10	30	95	0.35	20.0	5500857
13.0	22.0	10	30	95	0.35	40.0	5500858
16.0	25.0	10	30	110	0.41	20.0	5500859
16.0	25.0	10	30	110	0.41	40.0	5500860
19.0	29.0	10	30	135	0.54	20.0	5500861
19.0	29.0	10	30	135	0.54	40.0	5500862
25.0	36.0	10	30	180	0.74	20.0	5500863
25.0	36.0	10	30	180	0.74	40.0	5500864

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

