

# SUPERVRAC



## CONSTRUCTION & INFRASTRUCTURE

Bulk tank truck discharge



### APPLICATIONS

Pneumatic transport of bulk abrasive products.  
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

### ADVANTAGES

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

### COMPLEMENTARY INFORMATION

Can be used in ATEX zones.

### TECHNICAL DESCRIPTION

|                       |                                                  |
|-----------------------|--------------------------------------------------|
| Inner tube            | wear resistant NR, black, smooth.                |
| Reinforcement         | synthetic textile                                |
| Cover                 | weather resistant NR, black, fabric impression.  |
| Working temperature   | -30°C => +90°C.                                  |
| Electrical Properties | conductive tube and cover, $R < 10^6 \Omega/m$ . |

RAC




Made in Europe



TRELLEBORG

SUPERVRAC



| CONSTRUCTION & INFRASTRUCTURE |         | SUPERVRAC              |                         |  |            |                |
|-------------------------------|---------|------------------------|-------------------------|-----------------------------------------------------------------------------------|------------|----------------|
| ID (MM)                       | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | WEIGHT (KG/M)                                                                     | LENGTH (M) | ARTICLE NUMBER |
| 75.0                          | 88.5    | 7                      | 21                      | 1.83                                                                              | 20.0       | 0060675        |
| 75.0                          | 88.5    | 7                      | 21                      | 1.83                                                                              | 40.0       | 0060674        |
| 75.0                          | 93.0    | 7                      | 21                      | 2.75                                                                              | 20.0       | 0060189        |
| 75.0                          | 93.0    | 7                      | 21                      | 2.75                                                                              | 40.0       | 0060193        |
| 89.0                          | 101.5   | 7                      | 21                      | 2.07                                                                              | 20.0       | 0060682        |
| 89.0                          | 101.5   | 7                      | 21                      | 2.07                                                                              | 40.0       | 0060683        |
| 100.0                         | 112.0   | 7                      | 21                      | 2.40                                                                              | 20.0       | 0129701        |
| 100.0                         | 112.0   | 7                      | 21                      | 2.40                                                                              | 40.0       | 0129702        |
| 100.0                         | 118.0   | 7                      | 21                      | 3.58                                                                              | 20.0       | 0060194        |
| 100.0                         | 118.0   | 7                      | 21                      | 3.58                                                                              | 40.0       | 0060195        |
| 110.0                         | 123.0   | 7                      | 21                      | 2.77                                                                              | 20.0       | 0060684        |
| 110.0                         | 123.0   | 7                      | 21                      | 2.77                                                                              | 40.0       | 5006696        |
| 127.0                         | 144.0   | 7                      | 21                      | 4.20                                                                              | 20.0       | 0060685        |
| 127.0                         | 144.0   | 7                      | 21                      | 4.20                                                                              | 40.0       | 0060686        |
| 152.0                         | 169.0   | 7                      | 21                      | 5.00                                                                              | 20.0       | 0060689        |
| 152.0                         | 169.0   | 7                      | 21                      | 5.00                                                                              | 40.0       | 0060690        |

Tolerance on length: ±1% (ISO 1307 Standard).

