

TRUCK 10 SD



CONSTRUCTION & INFRASTRUCTURE

Bulk tank truck/Suction and discharge



APPLICATIONS

Suction and delivery hose to transfer abrasive material such as cement, sand, etc.

TECHNICAL DESCRIPTION

Inner tube	natural rubber, black, smooth.
Reinforcement	synthetic textile, embedded steel helix and antistatic wire
Cover	synthetic SBR rubber, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	conductive tube.
Special Properties	Max. vacuum: 0.9 bar.

SD



TRELLEBORG

TRUCK 10 SD





CONSTRUCTION & INFRASTRUCTURE

TRUCK 10 SD



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
76.0	98.0	10	30	320	4.10	40.0	5513675
90.0	108.0	10	30	360	4.18	40.0	5513676
102.0	126.0	10	30	410	5.90	40.0	5513677
127.0	153.0	10	30	510	8.80	40.0	5513678
152.0	178.0	10	30	610	10.40	40.0	5513679

