

SOLVYKLER II



GENERAL INDUSTRY

Multipurpose chemicals & hot water



APPLICATIONS

Designed for the pressurized transfer of a wide range of chemical products, including esters, ketones and alcohols, as well as air and water.

ADVANTAGES

- Hose cover resistant to splashing of corrosive chemicals.
- Free from silicone.
- Hose remains flexible within a wide temperature range.
- Cover's abrasion resistance improved.
- Can be used in ATEX zones.


TECHNICAL DESCRIPTION

Inner tube	chemical resistant EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	chemical and weather resistant EPDM, black, smooth.
Working temperature	-30°C => +100°C.
Electrical Properties	Conductive tube and cover, $R < 10^6 \Omega/m$. Transversal conductivity ensured through rubber layers. Can be used in ATEX zones.



TRELLEBORG

SOLVYKLER II - WP 20 bar - Made in France





GENERAL INDUSTRY

SOLVYKLER II



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	MAX LENGTH (M)	ARTICLE NUMBER
6.0	12.6	20	≥ 60	60	0.13	120	-
8.0	15.0	20	≥ 60	70	0.16	120	-
10.0	18.0	20	≥ 60	90	0.22	120	-
13.0	21.0	20	≥ 60	110	0.27	120	-
16.0	24.0	20	≥ 60	130	0.32	80	-
20.0	29.0	20	≥ 60	150	0.44	80	-
25.0	34.0	20	≥ 60	170	0.54	80	-

Tolerance on length: ±1% (ISO 1307 Standard).