

HYDRO'ECO



AUTOMOTIVE

Oil



APPLICATIONS

Diesel, leaded and unleaded petrol, RMA (environmental friendly petrol) pressure hose in automotive applications withstanding aromatic content exceeding 50%.

Oil and grease return lines in hydraulic systems.

Also suitably in other applications for oil, grease, air and water.

ADVANTAGES

Special oil and petrol resistant inner tube.

Excellent bending radius.

Flexible at low and high temperatures.

Resistant cover to wear, oil mist, weather and ozone, abrasion.

COMPLEMENTARY INFORMATION

Available in other lengths or packaging on request.

All standard stock items delivered on white bobbins with hole ID 55mm.

TECHNICAL DESCRIPTION

Inner tube	NBR/PVC, black, smooth.
Reinforcement	synthetic textile
Cover	NBR/PVC, black, smooth.
Temperature range	-30°C => +100°C



and embossed: week - year

**AUTOMOTIVE****HYDRO'ECO**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
4.0	11.0	10	30	30	0.11	20	0061636
5.0	12.0	10	30	34	0.13	20	0061637
6.0	12.0	10	30	38	0.12	20	0061638
7.0	13.0	10	30	45	0.13	20	0061639
8.0	14.0	10	30	52	0.14	20	0061640
10.0	17.0	10	30	62	0.20	10	5500140

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

