

CALIKLER HT



BULK MATERIALS HANDLING

Tank truck air line

APPLICATIONS

Air line from compressor/booster on all types of tanker lorries for bulk transport of powdered products.

ADVANTAGES

- Extremely flexible with very low bending radius.
- Suitable for all types of road tanker compressors/boosters.

- Can be supplied fitted with swaged couplings, conforming with transported materials specifications.

TECHNICAL DESCRIPTION

Inner tube	heat resistant EPDM, white, smooth.
Reinforcement	high temperature resistant textile with embedded steel helix
Cover	weather resistant EPDM, black, fabric impression.
Working temperature	-30°C => +180°C. Peaks at +240°C
Special Properties	Max. vacuum: 0.9 bar.



Mar Carlos VIII

TRELLEBORG



CALIKLER HT



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
50.0	64.0	3	18	125	1.81	20.0	0060213
50.0	64.0	3	18	125	1.81	40.0	0060212
55.0	68.0	3	18	140	1.84	20.0	0200589
55.0	68.0	3	18	140	1.84	40.0	0200588
60.0	73.0	3	18	150	1.98	20.0	0070666
60.0	73.0	3	18	150	1.98	40.0	0070667
70.0	84.0	3	18	210	2.63	40.0	0200590
75.0	90.0	3	18	225	2.96	20.0	0060215
75.0	90.0	3	18	225	2.96	40.0	0060214
89.0	103.0	3	18	310	3.26	20.0	0200593
89.0	103.0	3	18	310	3.26	40.0	0200592

Tolerance on length: \pm 1% (ISO 1307 Standard).

