

FISH PUMP



AGRICULTURE

Farm/Pumping fish



APPLICATIONS

Used for pumping fish in fish farms and fish processing factories.

2 levels of working pressure available :

- 2 bar
- 3 bar

ADVANTAGES

- Flexible hose design providing optimum characteristics for this application.
- Withstands rough handling.
- Without helix for discharge applications.

COMPLEMENTARY INFORMATION

Other lengths available on request.

TECHNICAL DESCRIPTION

Inner tube	wear resistant SBR/NBR, black, smooth.
Reinforcement	synthetic textile
Cover	weather resistant SBR/NBR, black, fabric impression.
Working temperature	-40°C => +80°C.



FP 3010



FP 2007



and in opposite:

**AGRICULTURE****FISH PUMP**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
254.0	261.0	2	7	3.05	40.0	5010364
254.0	263.0	3	10	4.06	40.0	2955660
254.0	265.0	3	10	5.12	40.0	2863290
305.0	312.0	2	7	3.66	30.0	0594432
305.0	312.0	2	7	3.66	40.0	0208009
305.0	312.0	3	10	3.83	40.0	2861070
305.0	314.0	3	10	5.03	40.0	2913530
305.0	316.0	3	10	6.30	40.0	2911310
355.0	362.0	2	7	4.25	30.0	0594424
355.0	362.0	2	7	4.25	40.0	0208025
355.0	362.0	3	10	4.44	40.0	2860840
355.0	364.0	3	10	5.84	20.0	1300190
355.0	364.0	3	10	5.84	40.0	2052650
355.0	366.0	3	10	7.30	40.0	5500653

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

