

# TRELLVAC Extractor LD



## MINING & QUARRIES

Evacuation and material handling hoses



### APPLICATIONS

Universal ducting hose for dust, wood chips, small particles and various types of gas.

### ADVANTAGES

Light and flexible.  
Excellent bending radius.  
Especially useful when low weight and easy handling are valued.

### COMPLEMENTARY INFORMATION

OD measured on top of corrugation.  
Can be used in ATEX zones.

### TECHNICAL DESCRIPTION

Inner tube	wear resistant SBR/NR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	wear and weather resistant SBR/NR, black, corrugated.
Temperature range	-40°C => +90°C
Electrical Properties	conductive tube and cover, $R < 10^6 \Omega/m$ .





ID (MM)	OD (MM)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
38.0	44.5	45	0.62	12	0025890
51.0	57.5	70	0.81	12	0025908
63.0	70.0	95	0.87	12	0025916
76.0	83.5	115	1.04	12	0025932
90.0	97.5	125	1.22	12	0025965
102.0	110.5	145	1.57	12	0025973
113.0	121.5	155	1.73	12	0025981
127.0	135.5	170	1.93	12	0026005
152.0	160.5	195	2.30	12	0026013
178.0	186.5	220	2.68	12	0026021
204.0	212.5	245	3.06	12	0026039

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

