


# TRELLJET 581



# CONSTRUCTION & INFRASTRUCTURE





### **APPLICATIONS**

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. The non-staining cover is also an advantage for use in food industry and public baths.

Suitable for mobile pressure washers, fixed installations and reel mounted applications.

#### **ADVANTAGES**

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

# **COUPLING/FITTINGS**

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

#### COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.

## **TECHNICAL DESCRIPTION**

Inner tube	NBR/SBR, black, smooth.
Reinforcement	steel, one braid.
Cover	SBR/NBR, blue, smooth.
Working temperature	-40°C => +150°C.



11 CT 1	STRUCTION &	TRE	LLJET 581				
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.4	11.7	400	1000	50	0.16	100.0	2910430
7.9	13.4	400	1000	60	0.19	100.0	2910440
9.5	15.5	400	1000	70	0.25	100.0	2910450
12.7	18.7	350	900	80	0.30	100.0	2910470

Tolerance on length: ±1% (ISO 1307 Standard).

