

# SUPERMINES



**GENERAL INDUSTRY**



RUBBER ITEMS

## APPLICATIONS

Extra heavy duty compressor hose for building sites, civil engineering projects, quarries, etc.

## ADVANTAGES

Highly resistance to fatigue, bending and twisting.  
 Excellent resistance to abrasion, atmospheric conditions and dragging over rough and oily surfaces.  
 Good cold flexibility.  
 Suitable for oxygen discharge (ID≤25mm only).  
 Visible cover (yellow in colour).

## TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, yellow, smooth for ID≤25mm and fabric impression for ID>25mm.
Temperature range	-30°C => +70°C
Electrical Properties	non-conductive tube and cover.



7-25mm



35-50mm

**GENERAL INDUSTRY****SUPERMINES**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
7.0	14.0	20	80	24.5	0.17	20	0072917
7.0	14.0	20	80	24.5	0.17	40	0072918
7.0	14.0	20	80	24.5	0.17	80	0072919
10.0	19.5	20	80	35.0	0.33	20	0072923
10.0	19.5	20	80	35.0	0.33	40	0072924
10.0	19.5	20	80	35.0	0.33	80	0072925
13.4	23.1	20	60	48.0	0.41	20	0072929
13.4	23.1	20	60	48.0	0.41	40	0072928
13.4	23.1	20	60	48.0	0.41	80	0072927
16.4	28.1	20	60	65.0	0.61	20	0072939
16.4	28.1	20	60	65.0	0.61	40	0072938
16.4	28.1	20	60	65.0	0.61	80	0072937
19.4	31.1	20	60	77.0	0.69	20	0072949
19.4	31.1	20	60	77.0	0.69	40	0072948
19.4	31.1	20	60	77.0	0.69	80	0072947
25.0	39.0	20	60	102.0	1.03	20	0072969
25.0	39.0	20	60	102.0	1.03	40	0072968
25.0	39.0	20	60	102.0	1.03	80	0072967
35.0	51.0	20	80	250.0	1.57	20	0072979
35.0	51.0	20	80	250.0	1.57	40	0072983
50.0	68.0	20	80	350.0	2.44	20	0072991
50.0	68.0	20	80	350.0	2.44	40	0072994

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

