

KLERIX



CONSTRUCTION & INFRASTRUCTURE

Drain and sewer cleaning



APPLICATIONS

For use in sewer cleaning water pressure applications.
Suitable for replacing hydraulic hoses used in this application.

ADVANTAGES

- Abrasion and weather resistant cover compound.
- Smooth cover, low friction.
- Long lengths.

COUPLING/FITTINGS

Hydraulic coupling.

COMPLEMENTARY INFORMATION

Delivered without couplings.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	steel, braided
Cover	SBR/NR, black, smooth.
Temperature range	-30°C => +80°C



TRELLEBORG



KLERIX - WP 200 BAR - QUARTER YEAR - Made in France



Embossed branding



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	23.0	200	500	70	0.45	40	0071107
13.0	23.0	200	500	70	0.45	60	0071108
13.0	23.0	200	500	70	0.45	80	0071109
13.0	23.0	200	500	70	0.45	100	0071110
19.0	31.5	200	500	95	0.82	40	5010435
19.0	31.5	200	500	95	0.82	60	0071113
19.0	31.5	200	500	95	0.82	120	0071116
25.0	38.1	200	500	110	1.14	60	0071117
25.0	38.1	200	500	110	1.14	80	0071118
25.0	38.1	200	500	110	1.14	100	0071119
25.0	38.1	200	500	110	1.14	120	0071120
32.0	45.9	200	500	150	1.57	60	0071121
32.0	45.9	200	500	150	1.57	80	0071122
32.0	45.9	200	500	150	1.57	100	0071123
32.0	45.9	200	500	150	1.57	120	0071124

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

