

VULPANE



GENERAL INDUSTRY



Welding hoses

APPLICATIONS

Rubber hose for LPG (gas cylinders, heaters, welding and LPG lines).

ADVANTAGES


- Flexible and light weight for easy handling.
- Long, safe service life.
- A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).
- Special, high quality rubber compounds.
- Very strong textile reinforcement giving high safety factor.
- Clear branding showing gas symbol and date of manufacture.

TECHNICAL DESCRIPTION

Inner tube	NBR/SBR, black, smooth.
Reinforcement	synthetic textile
Cover	EPDM, orange, smooth.
Working temperature	-30°C => +80°C.

STANDARD/APPROVAL

ISO 3821.





GENERAL INDUSTRY

VULPANE



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.3	12.0	20	60	55	0.12	20.0	0200010
6.3	12.0	20	60	55	0.12	40.0	0200009
6.3	12.0	20	60	55	0.12	100.0	5501202
6.3	12.0	20	60	55	0.12	120.0	0200008
8.0	14.0	20	60	65	0.15	40.0	0200012
8.0	14.0	20	60	65	0.15	50.0	5012645
8.0	14.0	20	60	65	0.15	60.0	5012708
8.0	14.0	20	60	65	0.15	80.0	0129712
8.0	14.0	20	60	65	0.15	100.0	5501203
8.0	14.0	20	60	65	0.15	120.0	0200011
9.0	16.0	20	60	70	0.18	20.0	0200551
9.0	16.0	20	60	70	0.18	40.0	0200552
9.0	16.0	20	60	70	0.18	120.0	0200553
10.0	17.0	20	60	75	0.20	20.0	0200016
10.0	17.0	20	60	75	0.20	25.0	5010110
10.0	17.0	20	60	75	0.20	40.0	0200015
10.0	17.0	20	60	75	0.20	100.0	5501204
10.0	17.0	20	60	75	0.20	120.0	0200014
20.0	27.5	20	60	130	0.37	40.0	5503077

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

