

# OIL 20 S



## OIL & GAS

Oil and petroleum/Oil cargo



### APPLICATIONS

Suction and delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%, mainly for oil platforms, marine fueling, storage tanks or other industrial facilities.  
Limited use for biofuels. Consult us.

### ADVANTAGES

- Weather, flame, oil projection, UV and ozone resistant.
- Up to 60m long.


### TECHNICAL DESCRIPTION

Inner tube	NBR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	CR, black, fabric impression.
Working temperature	-30°C => +85°C.
Electrical Properties	crossing antistatic wires and conductive tube, $R < 10^6 \Omega / \text{lg}$ .
Special Properties	Max. vacuum: 0.9 bar.



**TRELLEBORG**

**OIL 20 S**



and embossed: TRELLEBORG - OIL 20 S - ND - WP 20 bar - month/year - batch number

**OIL & GAS****OIL 20 S**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	32.0	20	60	76	0.79	60.0	59013072
25.0	38.0	20	60	100	0.97	60.0	59013074
32.0	46.0	20	60	128	1.24	60.0	59013075
38.0	52.0	20	60	152	1.50	60.0	59013077
51.0	65.0	20	60	204	1.97	60.0	59013078
63.0	79.0	20	60	252	2.80	60.0	59013079
76.0	92.0	20	60	304	3.45	60.0	59013080
102.0	122.0	20	60	408	5.85	60.0	59011981
127.0	153.0	20	60	509	9.41	60.0	59011982
152.0	180.0	20	60	760	13.21	60.0	59011983
203.0	237.0	20	60	1200	21.82	40.0	59013049
254.0	300.0	20	60	1500	36.29	12.0	59013050

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

