

# PULVEDUC



## AGRICULTURE



### APPLICATIONS

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.).

Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

### ADVANTAGES

- A high performance hose for extra heavy-duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Very good ageing and weather resistance.
- Abrasion resistant cover.
- Other lengths on request.

### COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 40m, at least 50% will be in fixed length mentioned in the table.

### TECHNICAL DESCRIPTION

|                     |                     |
|---------------------|---------------------|
| Inner tube          | SBR, black, smooth. |
| Reinforcement       | synthetic textile   |
| Cover               | SBR, black, smooth. |
| Working temperature | -30°C => +70°C.     |

### STANDARD/APPROVAL


EN ISO 1401, type C for ID<16mm, type B for ID ≥16mm.

ISO

TRELLEBORG



PULVEDUC EN ISO1401:2016 TYPE ND WP bar BP bar Made in France QUARTER/YEAR



and embossed: week/year



AGRICULTURE

PULVEDUC



| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 8.0     | 16.0    | 60                     | 240                     | 40                  | 0,18          | 40         | 5609494        |
| 8.0     | 16.0    | 60                     | 240                     | 40                  | 0,18          | 160        | 5609495        |
| 9.0     | 17.5    | 60                     | 240                     | 40                  | 0,20          | 40         | 5609496        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 40         | 5609497        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 50         | 5609498        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 60         | 5609499        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 100        | 5609500        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 160        | 5609501        |
| 10.0    | 18.5    | 60                     | 240                     | 45                  | 0,23          | 200        | 5609502        |
| 12.0    | 21.0    | 60                     | 240                     | 50                  | 0,27          | 40         | 5609503        |
| 12.0    | 21.0    | 60                     | 240                     | 50                  | 0,27          | 80         | 5609504        |
| 12.0    | 21.0    | 60                     | 240                     | 50                  | 0,27          | 120        | 5609505        |
| 12.0    | 21.0    | 60                     | 240                     | 50                  | 0,27          | 160        | 5609506        |
| 16.0    | 26.5    | 40                     | 160                     | 80                  | 0,43          | 40         | 5609507        |
| 16.0    | 26.5    | 40                     | 160                     | 80                  | 0,43          | 120        | 5609508        |
| 20.0    | 31.0    | 40                     | 160                     | 90                  | 0,56          | 40         | 5609509        |
| 20.0    | 31.0    | 40                     | 160                     | 90                  | 0,56          | 120        | 5609510        |
| 25.0    | 37.0    | 40                     | 160                     | 100                 | 0,71          | 40         | 5609511        |
| 25.0    | 37.0    | 40                     | 160                     | 100                 | 0,71          | 80         | 5609512        |

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

