

TRELLVAC OIL HD



CONSTRUCTION & INFRASTRUCTURE



APPLICATIONS

For sewer suction.
Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

ADVANTAGES

High resistance to abrasive environment and abrasive transportation media.
Suitable both for suction and pressure.

TECHNICAL DESCRIPTION

Inner tube	NBR/SBR, black, abrasion resistance, smooth.
Reinforcement	High tensile textile cord, steel wire helix
Cover	SBR/NR, black, wear and weather resistant, corrugated.
Working temperature	-30°C => +85°C
Electrical Properties	Built-in conductive wire (helix must be connected with couplings).





**CONSTRUCTION &
INFRASTRUCTURE**

TRELLVAC OIL HD



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
80.0	96.0	3	9	240	2.87	30.0	59021303
80.0	96.0	3	9	240	2.87	40.0	59021302
102.0	119.0	3	9	306	3.86	30.0	59021305
102.0	119.0	3	9	306	3.86	40.0	59021304
120.0	138.0	3	9	420	4.75	30.0	59021307
120.0	138.0	3	9	420	4.75	40.0	59021306
152.0	171.0	3	9	608	6.96	30.0	59021309
152.0	171.0	3	9	608	6.96	40.0	59021308

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).