

STEAM 6



OIL & GAS

Steam



APPLICATIONS

Low pressure steam hose.

ADVANTAGES

- Highly flexible.
- Resistant to abrasion.

COMPLEMENTARY INFORMATION

Other lengths on request

TECHNICAL DESCRIPTION

Inner tube	synthetic EPDM rubber, black, smooth.
Reinforcement	synthetic textile
Cover	synthetic EPDM rubber, black, fabric impression.
Working temperature	-30°C => +164°C.
Electrical Properties	R<1MΩ/Ig.

STANDARD/APPROVAL

EN ISO 6134:2017 type 1 class A.

ISO



TRELLEBORG

STEAM 6 - EN ISO 6134:2017 - 1A - STEAM - 6 BAR (0.6MPa) - 164°C - ND - Ω - 1Q-20





OIL & GAS

STEAM 6



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	33.0	6	60	190	0.69	40.0	5513647
25.0	40.0	6	60	250	0.96	40.0	5513648
32.0	48.0	6	60	320	1.26	40.0	5513649
38.0	54.0	6	60	380	1.45	40.0	5513650
51.0	69.0	6	60	500	1.86	40.0	5513651

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

