

# OIL 10 S



## OIL & GAS

Oil and petroleum/Suction and discharge applications



### APPLICATIONS

Suction and delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.  
Limited use for biofuels. Consult us.

### ADVANTAGES

- Weather, flame, oil projection, UV and ozone resistant.
- Up to 60m long.

### TECHNICAL DESCRIPTION


Inner tube	synthetic NBR rubber, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	synthetic NBR/SBR rubber, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	conductive tube, $R < 10^6 \Omega/m$ .
Special Properties	Max. vacuum: 0.9 bar.

**OIL 10 S**



**TRELLEBORG**

**OIL 10 S**



and embossed: TRELLEBORG - OIL 10 S - ND - WP 10 bar - month/year - batch number

**OIL & GAS****OIL 10 S**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	31.0	10	30	80	0.72	20.0	5514121
19.0	31.0	10	30	80	0.72	40.0	5514122
19.0	32.0	20	60	76	0.79	60.0	59013072
25.0	37.0	10	30	100	0.88	20.0	5514123
25.0	37.0	10	30	100	0.88	40.0	5514124
25.0	38.0	20	60	100	0.97	60.0	59013074
32.0	44.0	10	30	130	1.05	20.0	5514125
32.0	44.0	10	30	130	1.05	40.0	5514126
32.0	46.0	20	60	128	1.24	60.0	59013075
38.0	51.0	10	30	140	1.30	20.0	5514127
38.0	51.0	10	30	140	1.30	40.0	5514128
38.0	52.0	20	60	152	1.50	60.0	59013077
40.0	54.0	10	30	160	1.47	20.0	5514129
40.0	54.0	10	30	160	1.47	40.0	5514130
45.0	57.0	10	30	160	1.46	40.0	5514131
51.0	64.0	10	30	180	1.73	20.0	5514132
51.0	64.0	10	30	180	1.73	40.0	5514133
51.0	65.0	20	60	204	1.97	60.0	59013078
60.0	73.0	10	30	200	2.16	40.0	5514134
63.0	76.0	10	30	220	2.26	20.0	5514135
63.0	79.0	20	60	252	2.80	60.0	59013079
70.0	85.0	10	30	240	2.97	40.0	5514137
75.0	90.0	10	30	260	3.16	40.0	5514139
80.0	96.0	10	30	280	3.38	40.0	5514140
90.0	106.0	10	30	320	3.76	20.0	5514141
102.0	118.0	10	30	320	4.36	20.0	5514143
102.0	118.0	10	30	320	4.36	40.0	5514144
102.0	122.0	20	60	408	5.85	60.0	59011981
152.0	172.0	10	30	360	8.74	20.0	5514145
152.0	172.0	10	30	360	8.74	40.0	5514146
152.0	180.0	20	60	760	13.21	60.0	59011983

Tolerance on length: ±1% (ISO 1307 Standard).

