

NORMINES II



GENERAL INDUSTRY

Air and water



APPLICATIONS


Extra heavy duty air hose for pneumatic machine tools such as rock drills, grinding and poker machines, rivet and chipping hammers etc.
 All round multipurpose compressed air hose used in mining industries, building construction, plant industry and others.
 Suitable for compressed air in all applications, oxygen and inert gases.
 Also for other media (under certain conditions) such as industrial water, aqueous solutions or emulsions for horticultural spraying, white washing, disinfection, acids and alkalis.

ADVANTAGES


Very high resistance to abrasion and atmospheric conditions.
 Good cold flexibility.
 Wide range of diameters and dimensions.
 High safety factor.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, black, smooth for ID≤25mm, fabric impression for ID>25mm.
Working temperature	-40°C => +70°C.
Electrical Properties	antistatic tube and cover, R<100MΩ.



6-25mm



30-100mm

**GENERAL INDUSTRY****NORMINES II**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	13.0	20	80	18	0.16	20.0	0061336
6.0	13.0	20	80	18	0.16	40.0	0061337
6.0	13.0	20	80	18	0.16	120.0	0061338
8.0	15.0	20	80	25	0.19	20.0	0061342
8.0	15.0	20	80	25	0.19	40.0	0061343
8.0	15.0	20	80	25	0.19	120.0	0061344
9.0	17.0	20	80	30	0.25	20.0	0061345
9.0	17.0	20	80	30	0.25	40.0	0061346
9.0	17.0	20	80	30	0.25	120.0	0061347
10.0	18.0	20	80	35	0.26	20.0	0061348
10.0	18.0	20	80	35	0.26	40.0	0061349
10.0	18.0	20	80	35	0.26	120.0	0061350
13.4	22.5	20	80	60	0.40	20.0	5500055
13.4	22.5	20	80	60	0.40	40.0	5500056
13.4	22.5	20	80	60	0.40	80.0	5500057
16.4	27.6	20	80	70	0.61	20.0	5500058
16.4	27.6	20	80	70	0.61	40.0	5500059
16.4	27.6	20	80	70	0.61	80.0	5500060
19.4	30.6	20	80	80	0.69	20.0	5500061
19.4	30.6	20	80	80	0.69	40.0	5500062
19.4	30.6	20	80	80	0.69	80.0	5500063
25.0	38.0	20	80	100	1.01	20.0	5500064
25.0	38.0	20	80	100	1.01	40.0	5500065
25.0	38.0	20	80	100	1.01	80.0	5500066
30.0	42.0	20	60	300	1.00	20.0	0200202
30.0	42.0	20	60	300	1.00	40.0	0200201
32.0	44.0	20	60	320	1.06	20.0	0200205
32.0	44.0	20	60	320	1.06	40.0	0200204
35.0	48.0	20	60	350	1.26	20.0	0200208
35.0	48.0	20	60	350	1.26	40.0	0200207
38.0	51.0	20	60	380	1.35	20.0	0200307
38.0	51.0	20	60	380	1.35	40.0	0200308
40.0	54.0	20	60	400	1.54	20.0	0200214
40.0	54.0	20	60	400	1.54	40.0	0200213
50.0	66.0	20	60	500	2.13	20.0	0200220
50.0	66.0	20	60	500	2.13	40.0	0200219
60.0	76.0	20	60	600	2.51	20.0	0200223
60.0	76.0	20	60	600	2.51	40.0	0200222
63.0	79.0	20	60	650	2.64	20.0	0070489
63.0	79.0	20	60	650	2.64	40.0	0070490
75.0	91.0	20	60	750	3.03	20.0	0200227
100.0	116.0	20	60	1000	3.87	20.0	0070493

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

