

ABRA



CONSTRUCTION & INFRASTRUCTURE

Blasting and guniting



APPLICATIONS


Abrasive resistant sandblast hose used for the delivery of sand, steel shot, stone.

- 2 levels of working pressure available :
- 10 bar
 - 12 bar

TECHNICAL DESCRIPTION

Inner tube	NR, black, smooth.
Reinforcement	synthetic textile
Cover	abrasion resistant SBR, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	conductive tube.
Special Properties	abrasion resistance of tube <70mm3 according to ISO 4649.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	27.0	10	30	104	0.53	40.0	5513716
13.0	27.0	12	36	104	0.50	40.0	5513728
16.0	30.0	10	30	130	0.61	40.0	59006824
16.0	30.0	12	36	130	0.61	40.0	5513729
19.0	33.0	12	36	160	0.71	40.0	5513730
25.0	39.0	10	30	200	0.83	40.0	5513718
25.0	39.0	12	36	200	0.83	40.0	5513731
32.0	48.0	10	30	260	1.23	40.0	5513719
32.0	48.0	12	36	260	1.17	40.0	5513732
38.0	56.0	10	30	300	1.55	40.0	5513720
38.0	56.0	12	36	300	1.80	40.0	5513733
51.0	71.0	10	30	410	2.20	40.0	5513721
51.0	71.0	12	36	410	2.22	40.0	5513734
63.0	83.0	10	30	510	2.70	40.0	5513722
63.0	85.0	12	36	510	2.94	40.0	5513735
76.0	100.0	12	36	610	3.73	40.0	5513736

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

