

TRELLJET 580



CONSTRUCTION & INFRASTRUCTURE

Water/High pressure jetting



APPLICATIONS

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. The non-staining cover is also an advantage for use in food industry and public baths. Suitable for mobile pressure washers, fixed installations and reel mounted applications.

ADVANTAGES

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High working pressure.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.

TECHNICAL DESCRIPTION

Inner tube	NBR/SBR, black, smooth.
Reinforcement	steel, two braids.
Cover	SBR/NBR, blue, smooth.
Working temperature	-40°C => +150°C.





**CONSTRUCTION &
INFRASTRUCTURE**

TRELLJET 580



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
7.9	15.0	650	1600	65	0.31	100.0	2910310
9.5	17.4	650	1600	70	0.38	100.0	2910370
12.7	20.6	500	1200	70	0.47	100.0	2910420

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

