

VULCAIN +



GENERAL INDUSTRY

Air and water



APPLICATIONS

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

ADVANTAGES

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.

TECHNICAL DESCRIPTION

Inner tube	EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	EPDM, blue, smooth.
Working temperature	-40°C => +100°C.
Electrical Properties	conductive tube, $R < 10^6 \Omega/m$.





GENERAL INDUSTRY

VULCAIN +



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	12.0	20	80	25	0.11	20.0	0129662
6.0	12.0	20	80	25	0.11	40.0	0129663
6.0	12.0	20	80	25	0.11	120.0	0129665
7.0	14.0	20	80	25	0.15	20.0	0129667
7.0	14.0	20	80	25	0.15	40.0	0129668
7.0	14.0	20	80	25	0.15	120.0	0129669
8.0	15.0	20	60	30	0.16	20.0	0129670
8.0	15.0	20	60	30	0.16	40.0	0129671
8.0	15.0	20	60	30	0.16	120.0	0129672
9.0	16.0	20	60	35	0.18	20.0	0129673
9.0	16.0	20	60	35	0.18	40.0	0129675
9.0	16.0	20	60	35	0.18	120.0	0129676
10.0	18.0	20	60	40	0.23	20.0	0129678
10.0	18.0	20	60	40	0.23	40.0	0129679
10.0	18.0	20	60	40	0.23	120.0	0129680
12.0	20.0	20	60	60	0.26	20.0	5501021
12.0	20.0	20	60	60	0.26	40.0	5501020
12.0	20.0	20	60	60	0.26	120.0	5501019

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

