

ABRA 10



CONSTRUCTION & INFRASTRUCTURE

Blasting and guniting



APPLICATIONS

Abrasive resistant sandblast hose used for the delivery of sand, steel shot, stone.

TECHNICAL DESCRIPTION

Inner tube	NR, black, smooth.
Reinforcement	synthetic textile
Cover	abrasion resistant SBR, black, fabric impression.
Temperature range	-30°C => +80°C
Electrical Properties	conductive tube.
Special Properties	abrasion resistance of tube <70mm ³ according to ISO 4649.





**CONSTRUCTION &
INFRASTRUCTURE**

ABRA 10



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	27.0	10	30	104	0.53	40	5513716
16.0	30.0	10	30	130	0.61	40	59006824
25.0	39.0	10	30	200	0.83	40	5513718
32.0	48.0	10	30	260	1.23	40	5513719
38.0	56.0	10	30	300	1.55	40	5513720
51.0	71.0	10	30	410	2.20	40	5513721
63.0	83.0	10	30	510	2.70	40	5513722

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

