

FOOD 10 OIL SD



FOOD & BEVERAGE

Food industry
Transfer



APPLICATIONS

Food suction and delivery hose, suitable for oil and fats.

TECHNICAL DESCRIPTION

Inner tube: food grade, oil resistant NBR, white, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather and oil resistant PVC/NBR, blue, fabric impression.

Temperature range: -20°C to +85°C.


STANDARD/APPROVAL

FDA compliant tube.



TRELLEBORG

FOOD 10 OIL SD 



**FOOD & BEVERAGE****FOOD 10 OIL SD**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
19.0	30.0 ±1	10	30	0.9	80	0.65	40	5513694	1
25.0	36.0 ±1	10	30	0.9	100	0.87	40	5513695	1
38.0	50.0 ±1	10	30	0.9	160	1.22	40	5513696	1
51.0	64.0 ±1.2	10	30	0.9	200	1.76	40	5513697	1
63.0	77.0 ±1.2	10	30	0.9	240	2.3	40	5513698	1
76.0	90.0 ±1.2	10	30	0.9	320	2.89	40	5513699	160

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**