

# MULTIKLER



## GENERAL INDUSTRY

### PAINTING



### APPLICATIONS

Pressure service line for benzene, toluene and xylene based paints, lacquer, varnish and certain chemicals.  
Also for industrial paint spray equipment.

### ADVANTAGES

Hose cover resistant both to abrasion and to corrosive chemicals.  
Free from silicone.  
Antistatic tube.

### COUPLING/FITTINGS

Special paint hose couplings are recommended.

### TECHNICAL DESCRIPTION

Inner tube	solvent paints resistant NBR, black, smooth.
Reinforcement	synthetic textile
Cover	oil and weather resistant NBR/PVC, green, smooth.
Temperature range	-20°C => +100°C
Electrical Properties	antistatic tube, $R < 10^6 \Omega/m$ .


ce



TRELLEBORG



MULTIKLER





GENERAL INDUSTRY

MULTIKLER



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	12.6	20	60	60	0.14	40	0064197
6.0	12.6	20	60	60	0.14	80	0064198
6.0	12.6	20	60	60	0.14	120	0064199
8.0	15.0	20	60	70	0.17	20	0064201
8.0	15.0	20	60	70	0.17	40	0064202
8.0	15.0	20	60	70	0.17	80	0064203
8.0	15.0	20	60	70	0.17	120	0064204
10.0	17.5	20	60	90	0.24	20	0064207
10.0	17.5	20	60	90	0.24	40	0064208
10.0	17.5	20	60	90	0.24	80	0064209
10.0	17.5	20	60	90	0.24	120	0064210
13.0	21.0	20	60	110	0.28	20	0064211
13.0	21.0	20	60	110	0.28	40	0064212
13.0	21.0	20	60	110	0.28	80	0064213
13.0	21.0	20	60	110	0.28	120	0064214
16.0	25.0	20	60	130	0.38	40	0064216
16.0	25.0	20	60	130	0.38	80	0064217
16.0	25.0	20	60	130	0.38	120	0064218

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

