

AG 1000 HT



GENERAL INDUSTRY

Exhaust gas hoses



APPLICATIONS

Extraction of exhaust gases and other hot gases from motor vehicles.
For all types of spring recoil exhaust hose reels, exhaust fume extractors and also exhaust rails for moving vehicles.

ADVANTAGES

Extremely low weight and flexibility makes the hose especially suitable for manual handling.
Smooth inside reduces friction less.
Manufactured with a polyester helix as standard.
The polyester helix makes the hose regain original shape when ran over by motor vehicle.
Hose lengths can be connected by screwing them together.
Also available with steel helix in order to withstand higher vacuum.

COMPLEMENTARY INFORMATION

Packed in cartons.

TECHNICAL DESCRIPTION

Inner tube	heat resistant, rubberized fabric, EPDM/polyester, black.
Reinforcement	EPDM-coated polyester, black
Working temperature	-40°C => +180°C.
Special Properties	Max. vacuum: 0.6 bar Ø 32, 0.55 bar Ø 38, 0.5 bar Ø 45, 0.4 bar Ø 51, 0.3 bar Ø 63, 0.25 bar Ø 76, 0.2 bar Ø 102, 0.15 bar Ø 127, 0.1 bar Ø 152, 0.03 bar Ø 204.





GENERAL INDUSTRY

AG1000 HT



ID (MM)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
32.0	40	0.28	10.0	1977880
38.0	50	0.32	10.0	1977840
45.0	55	0.34	10.0	1977890
51.0	65	0.42	10.0	2860230
63.0	80	0.53	10.0	2210510
76.0	95	0.60	10.0	2059150
102.0	110	0.85	10.0	2059160
127.0	130	1.04	10.0	1693510
152.0	140	1.24	10.0	1692920
204.0	190	1.68	10.0	2955920

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

