

MULTI 20 HOT



GENERAL INDUSTRY

Hot water and multipurpose chemicals



APPLICATIONS

Multi-purpose hose, with very good ageing. Suitable for air, cold and hot water.

Also suitable for pressure service line for ester, ketone, alcohol based paints and numerous chemicals.

ADVANTAGES

- Hose cover resistant to splashing of corrosive chemicals.
- Free from silicone.
- Hose remains flexible within a wide temperature range.
- Conductive tube and cover.

TECHNICAL DESCRIPTION

Inner tube	EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	EPDM, black, smooth.
Working temperature	-30°C => +100°C.
Electrical Properties	conductive tube and cover, $R \leq 1M\Omega/1g$ ($R \leq 10^6\Omega/1g$).



TRELLEBORG

MULTI 20 HOT



GENERAL INDUSTRY

MULTI 20 HOT



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	13.0	20	80	40	0.14	40.0	5513859
8.0	15.0	20	80	50	0.17	40.0	5513860
10.0	17.0	20	80	60	0.19	40.0	5513861
13.0	21.0	20	80	80	0.28	40.0	5513862
16.0	24.0	20	80	100	0.33	40.0	5513863
19.0	28.0	20	80	115	0.43	40.0	5513864
25.0	35.0	20	80	150	0.61	40.0	5513865

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

