

# TRELLJET 561



## CONSTRUCTION & INFRASTRUCTURE

Water/High pressure jetting



### APPLICATIONS

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. Suitable for mobile pressure washers, fixed installations and reel mounted applications.

### ADVANTAGES

Smooth cover.  
Oil, detergent, wear and weather resistant.  
High temperature resistance.  
Light weight, flexible and kink resistant.  
Long service life.

### COUPLING/FITTINGS


Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.

### TECHNICAL DESCRIPTION

Inner tube	NBR/SBR, black, smooth.
Reinforcement	steelone braid
Cover	SBR/NBR, black, smooth.
Temperature range	-40°C => +150°C





**CONSTRUCTION &  
INFRASTRUCTURE**

**TRELLJET 561**



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.4	11.7	400	1000	50	0.16	100	2913930
7.9	13.4	400	1000	60	0.19	100	2910040
9.5	15.5	400	1000	70	0.25	100	2910000
12.7	18.7	350	900	80	0.30	100	5015696

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

