

OIL 10 S



OIL & GAS

Oil and petroleum/Suction and discharge applications



APPLICATIONS

Suction and delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.
Limited use for biofuels. Consult us.

ADVANTAGES

- Weather, flame, oil projection, UV and ozone resistant.
- Up to 60m long.

TECHNICAL DESCRIPTION


Inner tube	synthetic NBR rubber, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	synthetic NBR/SBR rubber, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	conductive tube, $R < 10^6 \Omega/m$.
Special Properties	Max. vacuum: 0.9 bar.

OIL 10 S



TRELLEBORG

OIL 10 S



and embossed: TRELLEBORG - OIL 10 S - ND - WP 10 bar - month/year - batch number

 OIL & GAS		OIL 10 S					
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	31.0	10	30	80	0.72	20.0	5514121
19.0	31.0	10	30	80	0.72	40.0	5514122
25.0	37.0	10	30	100	0.88	20.0	5514123
25.0	37.0	10	30	100	0.88	40.0	5514124
32.0	44.0	10	30	130	1.05	20.0	5514125
32.0	44.0	10	30	130	1.05	40.0	5514126
38.0	51.0	10	30	140	1.30	20.0	5514127
38.0	51.0	10	30	140	1.30	40.0	5514128
40.0	54.0	10	30	160	1.47	20.0	5514129
40.0	54.0	10	30	160	1.47	40.0	5514130
45.0	57.0	10	30	160	1.46	40.0	5514131
51.0	64.0	10	30	180	1.73	20.0	5514132
51.0	64.0	10	30	180	1.73	40.0	5514133
60.0	73.0	10	30	200	2.16	40.0	5514134
63.0	76.0	10	30	220	2.26	20.0	5514135
70.0	85.0	10	30	240	2.97	40.0	5514137
75.0	90.0	10	30	260	3.16	40.0	5514139
80.0	96.0	10	30	280	3.38	40.0	5514140
90.0	106.0	10	30	320	3.76	20.0	5514141
102.0	118.0	10	30	320	4.36	20.0	5514143
102.0	118.0	10	30	320	4.36	40.0	5514144
152.0	172.0	10	30	360	8.74	20.0	5514145
152.0	172.0	10	30	360	8.74	40.0	5514146

Tolerance on length: ±1% (ISO 1307 Standard).

