

TRELLVAC

Excavator



MINING & QUARRIES

Evacuation and material handling hoses



APPLICATIONS

Working hose specially designed for suction excavators.

ADVANTAGES

- Long lifespan thanks to the high quality NR tube and its large thickness.
- Easy replacement of the hose thanks to 254mm diameter.

COUPLING/FITTINGS

Cuffed or enlarged ends:

- length 5.3m: OD on cuffed end = 299mm,
- other lengths: OD on cuffed and enlarged end = 292mm.

COMPLEMENTARY INFORMATION

Hoses are delivered in straight length, on pallet.

Max vacuum : 0,9 bar

TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, red, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	SBR/NR, black, corrugated.
Working temperature	-30°C => +80°C.
Electrical Properties	Can be used in ATEX zones.
Special Properties	Max. vacuum: 0.9 bar.





MINING & QUARRIES

TRELLVAC EXCAVATOR



ID (MM)	OD (MM)	BENDING RADIUS (MM)	LENGTH (M)	ARTICLE NUMBER
254.0	300.0	500	6.9	59011152
254.0	300.0	500	6.9	59011879
254.0	300.0	500	7.9	59011153
254.0	307.0	500	5.3	59012748

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

