

MILLESIME



FOOD & BEVERAGE

Food industry/Transfer



APPLICATIONS

Suction and discharge of liquid foodstuffs such as milk, wine, beer, cider, fruit juice, soda, vinegar and alcohol up to 50% with exception of fatty foodstuffs and oils.
Particularly designed for additional air lines (temperature up to 140°C) on road tankers carrying bulk products.

ADVANTAGES

- Good flexibility and easy to handle.
- Suitable for road tankers equipment except compressor lines.
- A smooth, seamless, white food grade tube that does not propagate bacterial growth.
- Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 140°C.
- Cover with very good ageing and weather resistance.
- Contains no phthalate.

COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

COMPLEMENTARY INFORMATION

Please refer to our cleaning guidelines, available upon request and from our website.

TECHNICAL DESCRIPTION

Inner tube	food grade quality EPDM, white, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	weather resistant EPDM, blue, fabric impression.
Working temperature	-30°C => +100°C. +140°C for additional air
Special Properties	Max. vacuum: 0.9 bar.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

EU

FDA regulation No. 21 CFR 177.2600.

FDA

French legislation.

RF

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.



and embossed: TRELLEBORG - MILLESIME - FDA - ND - WP 10bar - week/year - batch number - Made in France

**FOOD & BEVERAGE****MILLESIME**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	36.0	10	30	55	0.75	20.0	5500495
25.0	36.0	10	30	55	0.75	40.0	5500496
32.0	43.0	10	30	70	0.92	20.0	5500497
32.0	43.0	10	30	70	0.92	40.0	5500498
38.0	49.0	10	30	80	1.07	20.0	5500499
38.0	49.0	10	30	80	1.07	40.0	5500500
40.0	51.0	10	30	85	1.12	20.0	5500501
40.0	51.0	10	30	85	1.12	40.0	5500502
45.0	56.0	10	30	98	1.23	20.0	5500505
45.0	56.0	10	30	98	1.23	40.0	5500506
51.0	62.5	10	30	105	1.59	20.0	5500507
51.0	62.5	10	30	105	1.59	40.0	5500508
53.0	64.5	10	30	110	1.64	20.0	5500509
53.0	64.5	10	30	110	1.64	40.0	5500510
60.0	71.5	10	30	125	1.85	20.0	5501050
60.0	71.5	10	30	125	1.85	40.0	5501051
63.0	74.5	10	30	130	1.93	20.0	5500511
63.0	74.5	10	30	130	1.93	40.0	5500512
70.0	81.5	10	30	145	2.14	40.0	5500514
76.0	88.5	10	30	165	2.65	20.0	5500515
76.0	88.5	10	30	165	2.65	40.0	5500516
89.0	102.0	10	30	330	3.18	20.0	5500517
102.0	115.0	10	30	400	3.62	40.0	5500522
125.0	145.5	10	30	480	6.59	20.0	5501068
150.0	171.5	10	30	570	8.05	10.0	5501069
150.0	171.5	10	30	570	8.05	20.0	5501070

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

