

OIL 10 D



OIL & GAS

Oil and petroleum/Discharge applications



APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.
Limited use for biofuels. Consult us.

ADVANTAGES

- Weather, flame, oil projection, UV and ozone resistant.
- Up to 60m long.

TECHNICAL DESCRIPTION


Inner tube	synthetic NBR rubber, black, smooth.
Reinforcement	synthetic textile
Cover	synthetic NBR/SBR rubber, black, fabric impression.
Working temperature	-30°C => +80°C.
Electrical Properties	conductive tube, $R < 10^6 \Omega/m$.

OIL 10 D



TRELLEBORG

OIL 10 D



and embossed: TRELLEBORG - OIL 10 D - ND - WP 10 bar - month/year - batch number

**OIL & GAS****OIL 10 D**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
16.0	26.0	10	30	130	0.45	40.0	5514101
19.0	31.0	10	30	160	0.60	40.0	5514102
25.0	37.0	10	30	200	0.74	40.0	5514103
30.0	41.0	10	30	300	0.78	40.0	5514104
32.0	44.0	10	30	320	0.90	20.0	5514105
32.0	44.0	10	30	320	0.90	40.0	5514106
35.0	46.0	10	30	350	0.89	40.0	5514107
38.0	51.0	10	30	380	1.17	20.0	5514108
38.0	51.0	10	30	380	1.17	40.0	5514109
40.0	54.0	10	30	400	1.34	40.0	5514110
45.0	59.0	10	30	450	1.48	40.0	5514111
51.0	65.0	10	30	510	1.65	20.0	5514112
51.0	65.0	10	30	510	1.65	40.0	5514113
60.0	74.0	10	30	600	1.80	40.0	5514114
63.0	75.0	10	30	630	1.66	40.0	5514115
75.0	90.0	10	30	700	2.44	40.0	5514116
76.0	92.0	20	60	304	2.42	60.0	5607748
80.0	95.0	10	30	760	2.58	40.0	5514117
90.0	105.0	10	30	800	2.88	40.0	5514118
102.0	115.0	10	30	900	2.82	20.0	5514119
102.0	115.0	10	30	900	2.82	40.0	5514120
102.0	118.0	20	60	815	3.77	60.0	59011978
152.0	172.0	20	60	1520	7.12	60.0	59011980

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

