

PULVEDUC



AGRICULTURE

Farm/Spraying



APPLICATIONS

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.).

Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

ADVANTAGES

- A high performance hose for extra heavy-duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Very good ageing and weather resistance.
- Abrasion resistant cover.
- Other lengths on request.

COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 40m, at least 50% will be in fixed length mentioned in the table.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, black, smooth.
Working temperature	-30°C => +70°C.

STANDARD/APPROVAL

EN ISO 1401, type C for ID<16mm, type B for ID ≥16mm.

ISO



TRELLEBORG

PULVEDUC EN ISO1401:2016 TYPE ND WP MPa / WP bar Made in France

and embossed: quarter/year

 AGRICULTURE PULVEDUC 							
ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
8.0	16.0	60	240	40	0,18	40.0	5609494
8.0	16.0	60	240	40	0,18	160.0	5609495
9.0	17.5	60	240	40	0,20	40.0	5609496
10.0	18.5	60	240	45	0,23	40.0	5609497
10.0	18.5	60	240	45	0,23	50.0	5609498
10.0	18.5	60	240	45	0,23	60.0	5609499
10.0	18.5	60	240	45	0,23	100.0	5609500
10.0	18.5	60	240	45	0,23	160.0	5609501
10.0	18.5	60	240	45	0,23	200.0	5609502
12.5	21.0	60	240	50	0,27	40.0	5609503
12.5	21.0	60	240	50	0,27	80.0	5609504
12.5	21.0	60	240	50	0,27	120.0	5609505
12.5	21.0	60	240	50	0,27	160.0	5609506
16.0	26.5	40	160	80	0,43	40.0	5609507
16.0	26.5	40	160	80	0,43	120.0	5609508
20.0	31.0	40	160	90	0,56	40.0	5609509
20.0	31.0	40	160	90	0,56	120.0	5609510
25.0	37.0	40	160	100	0,71	40.0	5609511
25.0	37.0	40	160	100	0,71	80.0	5609512

Tolerance on length: ±1% (ISO 1307 Standard).

