

SOLVYKLER



GENERAL INDUSTRY

Hot water and multipurpose chemicals



APPLICATIONS

Pressure service line for ester, ketone, alcohol based paints and numerous chemicals.

ADVANTAGES

Hose cover resistant to splashing of corrosive chemicals.
Free from silicone.
Hose remains flexible within a wide temperature range.
Antistatic tube.

COUPLING/FITTINGS

Special paint hose couplings are recommended.


TECHNICAL DESCRIPTION

Inner tube	chemical resistant EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	chemical and weather resistant EPDM, green, smooth.
Temperature range	-30°C => +100°C
Electrical Properties	antistatic tube, $R < 10^6 \Omega/m$.



TRELLEBORG

SOLVYKLER - Made in France





GENERAL INDUSTRY

SOLVYKLER



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	12.6	20	60	60	0.13	20	0060304
6.0	12.6	20	60	60	0.13	40	0060305
6.0	12.6	20	60	60	0.13	80	0060306
6.0	12.6	20	60	60	0.13	120	0060307
10.0	18.0	20	60	90	0.22	40	0060313
10.0	18.0	20	60	90	0.22	80	0060314
10.0	18.0	20	60	90	0.22	120	0060315
13.0	21.0	20	60	110	0.27	20	0060718
13.0	21.0	20	60	110	0.27	40	0060719
13.0	21.0	20	60	110	0.27	80	0060720
13.0	21.0	20	60	110	0.27	120	0060721
16.0	24.0	20	60	130	0.32	20	0070139
16.0	24.0	20	60	130	0.32	40	0070140
16.0	24.0	20	60	130	0.32	80	0070141
20.0	29.0	20	60	150	0.44	20	0070142
20.0	29.0	20	60	150	0.44	40	0070143
20.0	29.0	20	60	150	0.44	80	0070144
25.0	34.0	20	60	170	0.54	20	0070145
25.0	34.0	20	60	170	0.54	40	0070146
25.0	34.0	20	60	170	0.54	80	0070147

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

