

PROJECTOR 40



CONSTRUCTION & INFRASTRUCTURE

Spraying



APPLICATIONS

For spraying of mortar and mixed concrete as well as dry products. Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.
- Non-staining white cover avoids traces on walls and floors.

COMPLEMENTARY INFORMATION

2 standard colors available.
Type BK = Black
Type WH = White

TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, black, smooth.
Reinforcement	synthetic textile
Cover	wear and weather resistant SBR, black, fabric impression.
Working temperature	-30°C => +70°C.
Electrical Properties	conductive tube, $R < 2 \cdot 10^6 \Omega/m$.
Special Properties	abrasion resistance of tube $< 40mm^3$ according to ISO 4649.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	TYPE	ARTICLE NUMBER
25.0	44.0	12	40	120	1.20	40.0	BK	59006811
32.0	52.0	12	40	150	1.57	40.0	BK	59006812
40.0	60.0	12	40	180	1.80	20.0	BK	59006813
40.0	60.0	12	40	180	1.80	40.0	BK	59006814
50.0	70.0	12	40	250	2.22	20.0	BK	59006815
50.0	70.0	12	40	250	2.22	40.0	BK	59006816
60.0	80.0	12	40	290	2.30	20.0	BK	59006817
60.0	80.0	12	40	290	2.30	40.0	BK	59006818
63.0	90.0	12	40	340	2.83	20.0	BK	59006949
65.0	85.0	12	40	320	2.70	20.0	BK	59006819
65.0	85.0	12	40	320	2.79	20.0	WH	59006821
65.0	85.0	12	40	320	2.70	40.0	BK	59006820

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

