

PROJECTOR 40 WHITE



**CONSTRUCTION &
INFRASTRUCTURE**

Spraying



APPLICATIONS

For spraying of mortar and mixed concrete as well as dry products.
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES

Light weight, flexible and is easy to handle.
Abrasion resistant tube compound.
Conductive inner tube compound gives increased safety for the operator.
Non-staining white cover avoids traces on walls and floors.

TECHNICAL DESCRIPTION

Reinforcement	synthetic textile
Cover	wear and weather resistant SBR, white, fabric impression.
Temperature range	-30°C => +70°C
Electrical Properties	conductive tube, $R < 2.10^6 \Omega/m$.
Special Properties	abrasion resistance of tube <40mm ³ according to ISO 4649.



TRELLEBORG

PROJECTOR 40 WP 12 BAR





**CONSTRUCTION &
INFRASTRUCTURE**

PROJECTOR 40 WHITE



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
65.0	85.0	12	40	320	2.79	20	59006821

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

