

# PUMPADUKT D



## OIL & GAS

Oil and petroleum/Discharge for road and rail tankers



### APPLICATIONS

Discharge of petroleum products, especially designed for applications on reels.  
Road tanker equipment for oil delivery (aromatic content up to 50%).

### ADVANTAGES

Hose can be cut to length as required.  
Cover especially designed for oil, abrasion and weather resistance.  
Electrical conductivity ensured by the tube compound.  
In compliance with chemicals industry requirements.  
Suitable for biofuels up to 60°C.

### COMPLEMENTARY INFORMATION

ID>100mm: not included in EN 1761 and EN 12115 but designed, made and tested according to the same specifications required by both standards.

### TECHNICAL DESCRIPTION

Inner tube	oil and petrol resistant NBR, black, smooth.
Reinforcement	synthetic textile
Cover	oil and weather resistant CR, black, fabric impression.
Temperature range	-40°C => +100°C
Electrical Properties	conductive tube and cover, R<10 <sup>6</sup> Ω/Ig.

### STANDARD/APPROVAL

EN 1761:1999, EN 12115:2021.

EN



and embossed ID 19-100mm: TRELLEBORG - NBR1 - EN 12115:2021 - EN 1761:1999 - D - ND - WP 16bar - ? - -40 TO +100°C - quarter/year - batch number

and embossed ID 19-100mm: TRELLEBORG - NBR1 - EN 12115:2021 - EN 1761:1999 - D - ND - WP 16bar - Ω - -40 TO +100°C - quarter/year - batch number

and embossed ID 125-250mm: TRELLEBORG - NBR1 - EN 12115:2021 - EN 1761:1999 - D - ND - WP 12bar - Ω - -40 TO +100°C - quarter/year - batch number

**OIL & GAS****PUMPADUKT D**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	31.0	16	64	125	0.60	20	0070687
19.0	31.0	16	64	125	0.60	40	0070688
25.0	37.0	16	64	150	0.73	20	0070689
25.0	37.0	16	64	150	0.73	40	0095761
32.0	44.0	16	64	175	0.81	20	0060106
32.0	44.0	16	64	175	0.81	40	0126172
38.0	51.0	16	64	225	1.01	20	0123031
38.0	51.0	16	64	225	1.01	40	0125722
40.0	53.0	16	64	240	1.04	20	0070690
40.0	53.0	16	64	240	1.04	40	0123483
50.0	66.0	16	64	275	1.82	20	0127277
50.0	66.0	16	64	275	1.82	40	0124618
63.0	79.0	16	64	300	2.22	20	0070691
63.0	79.0	16	64	300	2.22	40	0123133
65.0	81.0	16	64	320	2.26	20	0070692
65.0	81.0	16	64	320	2.26	40	0070693
75.0	91.0	16	64	350	2.58	20	0070694
75.0	91.0	16	64	350	2.58	40	0125085
80.0	96.0	16	64	370	2.85	20	0070695
80.0	96.0	16	64	370	2.85	40	0070696
100.0	116.0	16	64	450	3.28	20	0125916
100.0	116.0	16	64	450	3.28	40	0123406
125.0	144.5	12	48	750	5.79	1	5514147
150.0	170.0	12	48	900	6.82	1	5601160
200.0	223.5	12	48	1400	10.84	1	5601203
250.0	273.0	12	48	1800	11.67	1	5514148

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

